

TKH | Siquira FD1103M1-I



Specificaties

3.0 Megapixelcamera

1/2.8" Progressive Scan CMOS

2.8-12 mm gemotoriseerde lens (30,5° ~ 94.5°)

Wide Dynamic Range functie (120dB), IR-filter

Lichtgevoeligheid 0 lux (IR leds 30m)

Resolutie: 45fps@3MP, 50fps@2MP, etc.

3 instelbare videostreams

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

VCA: Line crossing, Motion, Intrusion, Region entrance

Region exiting, Unattended baggage, Object removal

Micro SD/SDHC/SDXC slot, 128 GB

1-ch 3.5 mm Audio in (Mic in/Line in) / Audio uit

Omschrijving

De FD1103M1-I is een 3 megapixel IP dome camera met een 2,8-12mm gemotoriseerde lens. Met deze camera is het mogelijk om een Full HD 1080p stream 50 fps of een HD 2048 x 1536 @ 45 fps in te stellen. De camera is voorzien van intelligente VCA (Video Content Analyse) zoals Line crossing detection, Motion detection, Intrusion detection, Region entrance, Region exiting, Unattended baggage en Object removal. De geïntegreerde IR verlichting en de 120 dB wide dynamic range functie zorgen voor een goed beeld bij vrijwel alle licht omstandigheden. In combinatie met de wandbeugel is het mogelijk om de camera snel en netjes te installeren.

Accessoires



Nx1-004



Nx Witness