



25.6 cm (10.1) LCD/TFT Monitor LED backlight

- Displays a full, flat 10.1" (25.6cm) diagonal image
- High Contrast Ratio
- Metal cabinet
- Tempered glass
- USB interface



DIMENSIONS (mm)

PLUGS



TECHNICAL SPECIFICATIONS

Pixels - Total:	1280 (H) x 800 (V)
Pixel Pitch:	0.1695 mm(H) x 0.1695 mm(V)
Aspect Ratio:	16 : 10
Video Standard:	PAL/NTSC
Video Inputs:	1x Composite, BNC, 1x HDMI, 1x S-Video, 1x VGA
Backlight:	LED backlight
Viewing Angle:	176°(H) ~ 176°(V)
Contrast ratio:	500:1
Brightness:	400 cd/m ²
Response Time:	8 ms
Number of Colours:	16.7 million
Display protection:	Tempered Glass
OSD:	Yes, multi language
Serial Interface(s):	USB
Operating Temperature:	0°C ~ +50°C
Storage Temperature:	-20°C ~ +60°C
Accessories included:	Table stand bracket & PSU & VGA cable
MTBF at 25° C:	> 50,000 hours
Vesa Mount:	75 x 75 mm
Supply Voltage:	12 VDC, (100~240 VAC, 50/60Hz)
Dimensions (W x H x D):	231 x 178 x 50 mm - 9.09 x 7.01 x 1.97 In:
Power Consumption (W):	8
Weight:	1.71 kg - 3.77 lbs