

GCT-K1256P

2 MP Full HD Outdoor Motorized Dome TVI-Camera 23x Zoom ICR IR LED

- Full HD, 1920 x 1080p, 30/25 fps over coax
- 23x motorized optical zoom with 16x digital zoom
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Integrated IR LEDs 150m range
- Weatherproof Outdoor Installation (IP66)
- High Speed Pan/Tilt (400°/sec), minimum speed (0.5°/sec)



ACCESSORIES

GBR-WA08 GBR-WA08C GBR-WA08J GBR-WA08P



GBR-WA08JC GBR-WA08JP GBR-PA08 GBR-CE08L



FOR A GOOD REASON

GRUNDIG

TECHNICAL SPECIFICATIONS

Image Sensor:	1/2.8" Progressive Scan CMOS
Pixels - Total:	1920(H) x 1080(V)
Sensitivity Colour:	0.05 Lux@F1.4
Sensitivity B/W:	0.005 lux@F1.4
Col/B:	Auto, IR-cut filter removable (ICR)
Shutter Speed:	1 ~ 1/10,000 sec
Lens Focal Length:	4 ~ 92 mm
Viewing Angle:	49°(Wide) ~ 2.2°(Tele)
Lens Drive Type:	Auto iris (DC)
Digital Zoom:	16x
Max. IR Distance:	150 m
Pan Speed:	Manual: 0.1°/s ~ 400°/s, Preset: 400°/s (max.)
Tilt Speed:	Manual: 0.1°/s ~ 120°/s, Preset: 200°/s (max.)
Range Panning:	360° endless
Range Tilting:	-15° ~ 90° (auto flip)
Number of Preset:	256
Sequence:	8
AGC:	Auto, Manual
S/N Ratio:	>50 dB
Number of Privacy Zones:	8
White Balance:	Auto, Manual, Indoor, Outdoor, ATW
OSD:	English, Yes
Video Outputs:	1 CH HD-TVI (BNC)
Alarm Inputs:	2
Alarm Outputs:	1
Serial Interface(s):	1x RS-485
Protection Rating:	IP66
Certifications:	CE, IP66, RoHS
Operating Temperature:	-30°C ~ +65°C
Humidity:	less than 90%, non condensing
Supply Voltage:	24 Vac
Power Consumption (W):	30
Weight:	4 kg - 8.82 lbs
Dimensions:	185 x 330 mm - 7.28 x 12.99 In