



1.3 Megapixel HD Box Camera ICR WDR 12VDC/24VAC

- 1.3 Megapixel Sony® Exmor™ sensor with 1000 TVL highest resolution (analog) and superior low light performance
- 3x to digital zoom without loss of resolution
- Tampering detection shows text in the image "Anti Blocking" or "Anti Shifting"
- Intelligent Video Content Analysis with Motion Tracking
- Remote Control Interfaces over Coax (Coaxitron)
- Support Dual Power AC24V/DC12V



DIMENSIONS (mm)

ACCESSORIES

GBR-WA03



Image Sensor:	1/3" CMOS Sony Exmor 1.3 Megapixel
Scanning System:	PAL, 50Hz or NTSC, 60 HZ, selectable
Pixels - Effective:	1296(H) x 1032(V)
Co/B:	Auto, Color, Removable IR-Cut Filter (ICR)
Sensitivity Colour:	0.4 Lux(50IRE) @ F1.2 (SensUp=0, AGC Off), 0.0001Lux (50IRE) @ F1.2(AGC.Max., SensUpx64)
High Speed Shutter:	1/50 ~ 1/60.000 sec, auto, Antiflicker
S/N Ratio:	>50dB (AGC off)
Lens Mount:	C/CS mount with adaptor
Lens Drive Type:	Auto Iris (DC), Manual iris
Sens up:	Off ~ x64 auto
AGC:	0-20 adjustable
WDR:	>=96dB
De-Fog:	Off/On
BLC Back Light:	On/Off/HLC
White Balance:	ATW, AWB, AWC, Manual
Digital Noise Reduction:	3D-DNR : Off/Low/Mid/High
Digital Zoom:	Off ~ 8x
Motion Detection:	On/ Off/ Sensitivity/ 4 Area setting
Number of Privacy Zones:	16 programmable zones
Intelligent Video Analytics:	Scene change detection, masking of the camera lens
On Screen Alarm Information:	On camera shaking: "Unknown Motion", on brightness change "Blocking!!"
Motion Tracking (Quick Zoom):	On/Off
Lens Shading Compensation:	On/Off
Reverse:	Off/ H-REV/ V-REV
OSD:	Yes, EN/FR/DE
Profile Presets:	Indoor, Outdoor, Elevator, Lobby, Low, High, Hallway
Remote Control:	Coaxitron, data on coax cable
Video Outputs:	1 Ch Composite BNC, 1 Test monitor 2-pin connector
Humidity:	less than 95%
Operating Temperature:	-10°C ~ +50°C
Supply Voltage:	12 VDC / 24 VAC
Power Consumption (W):	3
Weight:	0,37 kg - 0 lbs