



IAD-5SG1004MUA

Article number: 216469

Gigabit Switch, Unmanaged, 60W, 4x PoE, 2x RJ45, 10/100/1000 Mbps, Desktop

Main features

Gigabit PoE switch, desktop application

PD (PoE Powered Devices) pass-through functionality

4x 10/100/1000 PoE ports, IEEE 802.3af / at

Surge protection IEC61000-4-5 (6KV)

Temperature range -10 ° C ~ + 45 ° C

2x Gigabit Uplink / PD Ports RJ45

PD port can be powered with max. 60W

Up to 30W per port, total ≤60W

CCTV mode allows transmission up to 250m @ 10Mbps

Power supply included

Specifications

Port mirror	no
QoS	no
SNMP	no
Network:	
Internal switching capacity (Mpps)	8,9Mpps
Internal switching capacity (Gbit/s)	12Gbps
VLAN	no
Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Ports	4x 10/100/1000Base-T, 2x 10/100/1000Base-TX
General:	
Dimensions (HxWxD)	27x135x86mm
Number PoE ports	4
Model	housing

IAD-5SG1004MUA

Continued Specifications

Switch type	Layer2 switch
Weight	350g
Power consumption	60W
Blower	no
Management	no
Mounting	desktop
PoE Power	60 W
Power over Ethernet	IEEE 802.3at
Supply voltage	PoE+
Temperature range (operation)	-10°C ~ +45°C
Scope of delivery:	
Parts supplied	manual, power cord, Mounting Bracket, PSU
Notes:	
Application	indoor
Support standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE), IEC61000-4-2, IEC61000-4-5

IAD-5SG1004MUA

Available Accessories

Image	Prod. No / Label	Description
	211978 / EFC-S1310SFP	SFP Modul, Gigabit, 10km, Singelmode 1310nm, Duplex LC Connector
	216477 / SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C
	216478 / SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
	216479 / SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
	216566 / SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
	216567 / SFP-0850MM10	SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
	216568 / NE-60PoE	PoE Injector, 60W, for Switch IAD-5SG1004MUA

Your Contact Person



eneo is a registered trademark of
 VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Deutschland
 Tel.: +49 6074-888-333
 E-Mail: info@eneo-security.com
 Web: www.eneo-security.com