



IAD-5SG1008MUA

Article number: 216472

Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Mainfeatures

Gigabit PoE Switch, desktop application

8x 10/100/1000 PoE Ports, IEEE 802.3af/at

ESD protection IEC61000-4-2 Standard

Brackets and 150W power-adaptor scope of supply

Gigabit Uplink Ports: 1x RJ45, 1x SFP

Up to 30W per Port, Total ≤120W

CCTV mode allows transmission up to 250m @ 10Mbps

Specifications

Port mirror	no
QoS	no
SNMP	no
Network:	
Internal switching capacity (Mpps)	14,9Mpps
Internal switching capacity (Gbit/s)	20Gbps
VLAN	no
Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Ports	8x 10/100/1000Base-T, 1x 1000Base-X SFP, 1x 10/100/1000Base-Tx
Optical connection	SFP Port
General:	
Dimensions (HxWxD)	27x200x101,8mm
Number PoE ports	8

IAD-5SG1008MUA

Continued Specifications


Model	housing
Switch type	Layer2 switch
Weight	500g
Blower	no
Management	no
Mounting	desktop
PoE Power	120 W
Power over Ethernet	IEEE 802.3at
Temperature range (operation)	-10°C ~ +45°C
Scope of delivery:	
Parts supplied	manual, ethernet cable, Mounting Bracket, PSU
Notes:	
Support standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE), IEC61000-4-2, IEC61000-4-5

IAD-5SG1008MUA

Available Accessories

Image	Prod. No / Label	Description
	211978 / EFC-S1310SFP	SFP Modul, Gigabit, 10km, Singelmode 1310nm, Duplex LC Connector
	216477 / SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C
	216478 / SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
	216479 / SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
	216566 / SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
	216567 / SFP-0850MM10	SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com