



IER-38R320005A

Article number: 217349

Network Video Recorder, 32x IP, H.265, H.264, 320Mbps, w/o HDD, HDMI, 16x PoE

32-channel network video recorder	CMS administration software included
Easy installation with eneo IP cameras	Smartphone app for video monitoring / configuration
Compression Method: H.264, H.265	16x alarm input and 1x alarm output
Resolution IP cameras up to 8 megapixels	16x PoE port (IEEE802.3af), total power 130W
Warp: Monitor and remote control of additional recorders	Support Dewarping Funktion (ISD-55P0010P0A)
Memory expandable via iSCSI and eSATA	1x HDMI monitor output with 4K UHD resolution

Specifications

Video:	
Compression standard	H.264, H.265
Display:	
Playback	full screen, 4 channel split, 9 channel split, 16 channel split, 32 channel split, split sequence
Live Display	3840x2160, 1920x1080, 1024x768, 1280x720, max. 960fps
Recording:	
Max. recording resolution	3840x2160
Max. recording rate	960 fps
Recording	permanent, timer, movement, contact, panic, PoS-Text, event
Pre-alarm recording	up to 5sec.
Backup	Setup
Export of images or clip	USB-port external HDD, via client software, AVI, H4V, MP4 via eneo Center
Features:	
Motion detector	integrated
Analysis functions	activity detection
Alarm notification	e-mail notification, alarm output, remote software, Live Popup, Buzzer, PTZ Preset, FTP, Push (Mobile)
Alarm triggers	disk error, eystem error, video loss, motion detection, PoS-Text, contact
Audio support	yes
Password protection	user control
HDD hotswap	no
Menu languages	English, German, French, Italian, Dutch, Chinese
Remote access	remote software, iPhone, Android, WEB Browser (java)
Search function	date/time, event, Thumbnail, text, museum, Instant Playback, VCA search
Covert camera mode	yes
Network:	
Network	1x 10/100/1000 Base-T RJ45
Network connection	WAN 1 x 10/100/1000BASE-T, 16x PoE RJ45 10/100 Base-T
Network protocols	TCP/IP, DHCP, Zeroconf, IPv4, IPv6, HTTP, UPnP, ARP, SMTP, RTSP, RTP, FTP, NTP
Data transfer rate	896 Mbps
Data transfer incoming	320 Mbps
Data transfer outgoing	576 Mbps

Interfaces / Inputs / Outputs:	
IP channels	32
Monitor outputs	HDMI, VGA
Spot monitor	no
USB ports	2x USB 2.0, 1x USB 3.0
Interfaces external storage	eSATA, iSCSI
Alarm inputs	16
Alarm output	1
Audio output	line output, HDMI
Serial interfaces	RS-485
System requirements:	
Operation system	Linux
General:	
Dimensions (HxWxD)	89.5x440.5x410mm
19" Rack mountable	yes
Number of HDD slots	4x SATA
Control units (external)	mouse, system keyboard, remote control
Harddisk capacity (internal)	0 TB
Max. harddisk capacity (internal)	32 TB
Weight	5.1kg
Integrated writer	no
Power consumption	165W
Remote Software	eneo Center
ONVIF	yes
PoE Power	130 W
Power over Ethernet	IEEE 802.3at
RAID	n/a
Supply voltage	100-240VAC
Temperature range (operation)	0°C ~ +45°C
Scope of delivery:	
Parts supplied	remote viewer software, PSU, manual, HDD assembly-kit, mouse, 19" rack mount angle
Notes:	
Firmware update	via remote software, USB

Related Products



HDD-3000SATA Purple|SKU: 217657




HDD-2000SATA Purple|SKU: 217658



HDD-4000SATA Purple|SKU: 217659



HDD-6000SATA Purple|SKU: 217660



eneo Center|SKU: 217368

More product information

ADUP (Archive Dual User Permission): dual authentication to access search, playback and backup. Users of this feature should have administrator rights.

Product recommendations



CON-HDD eneo | SKU: 216959



IEM-38R640005A | SKU: 217651



HDD-8000SATA Purple | SKU: 218583



KBD-2USB | SKU: 217652

