



VS27.0LEDFHD

27" 16:9 LED Paneel

VS27.0LEDFHD

| | |
|-------------------------------|---|
| Panel Type | 27" 16:9 LED Panel |
| Case Type | Plastic |
| Maximum Resolution | 1920(H) x 1080(V) |
| Active Display Area | 597.6(H) x 336.15(V) mm |
| Pixel Pitch | 0.31125(H) x 0.31125(V) mm |
| Bezel Thickness | Left/Right 27.6mm, Top 29.8mm, Bottom 42mm |
| Contrast Ratio | 1000:1 |
| Brightness | 300cd/m2 |
| Response Time | 5ms |
| Viewing Angle | 170°/160° H/V |
| Display Colours | 16.7M |
| Video Synchronization | Yes |
| PC Compatible Frequency | 30-60KHz(H)/56-75KHz(V) |
| Adjustable Colour Temperature | 9300K/6500K/5800K/User |
| Video Compatibility | NTSC/PAL |
| Aspect Ratio | 16:9 |
| VGA Auto Frequency correction | Yes |
| Speaker | 2 x 5w |
| Number of Speakers | 2 |
| Sound Demodulation | Audio, Stereo |
| Mute | Yes |
| Work Humidity | 5% - 90% |
| Work Temperature Volume +/- | -10°/+50° |
| Power On/Off | Yes |



POWER

| | |
|-------------------|------------------------|
| Power Supply | Built In |
| Voltage | AC110V - 240V 50/60 Hz |
| Power Consumption | < 40W. |

OSD CONTROLS

Contrast, Brightness, Colour, Sharpness, Colour Temperature

OSD LANGUAGE

English, German, Italian, Spanish, French, Russian, Portuguese and Polish

ACCESSORIES

HDMI Cable, User Man.
Power Lead

IN/OUT INTERFACE

| | |
|----------------------|--|
| Video Interface | 1x BNC Composite In, 1x BNC Composite Out, 1x VGA, 1x HDMI |
| Audio Interface | 1x PC Audio |
| Power Interface | DC In x 1 |
| Termination | 75 Ohms |
| Safety & EMC | CE, RoHS, FCC-DOC |
| Certification Vesa | 100mm x 100mm |
| Standard Mount Stand | Desktop |
| Type | Black |
| Colour | Black |
| Button Position | Front Face, Bottom |
| Packing Dimension | 740 x 165 x 570 mm |
| NET Weight | 6.05 Kg |

