



IEB-74M2812MAA

Article number: 219588

1/3" Network Camera, 2592x1520, Day&Night, WDR, 2,8-12mm, Infrared, IP66

1/3" OmniVision CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 2592x1520, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 2,8-12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, T-WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec	ONVIF Profile S conformity

Specifications

Camera:		Features:	
Camera type	Bullet	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Sensor size	1/3"	User interface	Type B (white / blue)
Resolution standard	4 Megapixel	Mirror function	H-flip, mirror
Imager	CMOS, OmniVision Sensor 4689	Digital Noise Reduction (DNR)	yes
System	True Day&Night	Network:	
Sensitivity	0,14 Lux, at F1.6, 40IRE	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Low speed shutter	yes, automatic	Interfaces / Inputs / Outputs:	
Manual electronic shutter (MES)	1~1/20.000sec.	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Automatic electronic shutter (ESC)	1~1/20.000sec.	Ethernet interface	10Base-T, 100Base-TX
Wide Dynamic Range (WDR)	WDR 120dB	Alarm inputs	1
Flickerless function	yes	Alarm outputs	1
Backlight compensation	Smart BLC	Serial interfaces	Ethernet
Day/Night switching	day, night, auto	General:	
IR cut filter	switchable	Series	SN-Series
White balance	automatic, manual	Dimensions (HxWxD)	86x90x279mm
Video:		Illumination	infrared, 34x LED 850nm
Resolution	2592x1520 (16:9), 2560x1440 (16:9), 2304x1296 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 720x576 (4:3), 720x480 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	Illumination range	approx. 30m
Resolution max.	2592x1520	Colour (housing)	white
Stream types	Quad Streaming	Housing	outdoor
Image transmission rate max.	30 fps	Housing material	aluminium
Multicast compliant	yes	Weight	860g
Compression standard	H.264, H.265, H.264+, H.265+, M-JPEG	Heater	no
Lens:		Integrated wall mount	yes
Lens type	Varifocal (motorized)	Power consumption	9W
Zoom factor	4x	Blower	no
Focal length	2,8 - 12 mm	Mounting	wall mount, ceiling mount
Digital zoom	yes	ONVIF	ONVIF Profile S, ONVIF Profile T
MOD (Minimum object distance)	0,5 m	Power over Ethernet	IEEE 802.3af
Iris control	P-iris, DC	Window heater	no
Vertical angle of view	55 - 18 °	Protection rating	IP66
Horizontal angle of view	97 - 31 °	SDK	upon request
Features:		Hidden cable management	yes
Motion detector	yes	Sunshield	yes
Analysis functions	activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector	Supply voltage	12VDC, PoE
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out	Temperature range (operation)	-20°C ~ +50°C
Audio	2 Way Audio	Text display	supplied
Audio support	yes	Vandalism resistant	no
Password protection	yes	Scope of delivery:	
e-PTZ support	yes	Parts supplied	manual, eneo Site Manager, bag of screws
Internal storage	microSDHC card, microSDXC card	Notes:	
Menu languages	English, German, French, Russian, Chinese, Korean, Japanese	Remarks	Note that electronic adjustment aid such as Zoom / Focus or Pan / Tilt functions are not designed for continuous operation. Permanent use may affect the life of the camera
Privacy zones masking	Areas-ON/OFF switchable		
Remote configuration	web browser		

Related Products



VT-PS12DC-10|SKU: 70543



AK-8|SKU: 219057



AK-9|SKU: 219058

Product recommendations



IAR-7SE1024MMA|SKU: 214460



IAM-5SE1008MUA|SKU: 214459



IAM-5SG1008MMA|SKU: 216129



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



IAR-7SG1008MMA|SKU: 216473



IAR-7SG1016MMA|SKU: 216474



IAR-7SG1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

