



VM-UHD28P

Article number: 228282

28" (71 cm) LCD Monitor, 4K UHD, 3840x2160, LED, USB, DisplayPort, HDMI

Professional 28"(71cm) LCD monitor	Built to run 24x7x365 continuously
Maximum resolution 4K UHD 3840x2160 pixels	Different video inputs DisplayPort, HDMI
LED Back Light	Built-in speakers
High brightness, High contrast	Including stand
Perfect presentation through digital 3D filtering and noise reduction	Plastic housing

Specifications

Display:	
Resolution	3840x2160 (16:9)
Synchronization	internal
Aspect ratio	16:9
Resolution pixels	3840x2160
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	350 cd/m ²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	28"
Screen Size (cm)	71 cm
Pixel format	0,1617mm x 0,1617mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, DisplayPort
Audio inputs	1x 3.5mm jack, 2
General:	
Dimensions (HxWxD)	380,16x659,15x17,58mm
Total height with stand	460mm
Mount	VESA standard 100x100mm
Housing material	metal / plastic
Housing color	black
Weight	7 kg
Loudspeaker	2
Power consumption	40W
Supply voltage	100 ~ 240VAC, 50/60Hz
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, power cord, feet, IR remote controller

Related Products



VM-LCDWMB1 | SKU: 224228



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

