



IPD-65M2713P5A

Article number: 227053

1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, Indoor

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 2592x1944, 5 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~13.5mm	Micro SD Card, HTML5 replay
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
VCA (Video Content Analysis), ONVIF event mapping	Wedge adapter included (10° inclination)
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:		Features:	
Camera type	Dome	Password protection	yes
Sensor size	1/2.8"	e-PTZ support	yes
Resolution standard	5 Megapixel	Internal storage	microSDHC card, microSDXC card
Imager	CMOS, Sony STARVIS, Sensor IMX335	Menu languages	English, German, French, Korean
System	True Day&Night	Privacy zones masking	Areas-ON/OFF switchable
Sensitivity	0,05 Lux, at F1.6, 40IRE	Remote configuration	web browser
Low speed shutter	yes, 1x-10x	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	User interface	Type A (orange / grey)
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Mirror function	mirror, flip
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Digital Noise Reduction (DNR)	yes
Flickerless function	yes	Network:	
Backlight compensation	BLC, HLC	Network protocols	TCP/IP, UDP, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	Interfaces / Inputs / Outputs:	
IR cut filter	switchable	Video outputs	no
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	External connections	micro SD card slot, RJ-45, 12VDC power input, connection cable approx.55cm
Signal-to-noise ratio	50dB	Ethernet interface	10Base-T, 100Base-TX
Video:		Alarm inputs	no
Resolution	2592x1944 (4:3), 2592x1520 (16:9), 2560x1440 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Alarm outputs	no
Resolution max.	2592x1944	Serial interfaces	Ethernet
Image display	VerticalView 90°/270°, 4:3, 16:9	General:	
Stream types	Multi Streaming	Series	eneo Callisto Indoor, eneo LN-Series
Image transmission rate max.	30 fps	Dimensions (HxWxD)	94x116mm
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Illumination	infrared, 2x High Power LEDs 850nm
Lens:		Illumination range	approx. 30m
Lens type	Varifocal (motorized)	Colour (housing)	white
Zoom factor	4x	Colour (bubble)	clear
Focal length	2,7 - 13,5 mm	Housing	indoor
Digital zoom	yes	Housing material	plastic
MOD (Minimum object distance)	0,5 m	Weight	300g
Iris control	DC	Heater	no
Vertical angle of view	54 - 17 °	Power consumption	8,5W
Horizontal angle of view	97 - 29 °	Blower	yes
Features:		Mounting	wall mount, ceiling mount
Multicast compliant	yes	ONVIF	ONVIF Profile S, ONVIF Profile T
Motion detector	yes	Power over Ethernet	IEEE 802.3af
Analysis functions	motion detection, Field detection, Defog, Object left,removed, Line detection	SDK	upon request
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping	Supply voltage	12VDC, PoE
Rotation range	+/-165 °	Temperature range (operation)	-10°C ~ +50°C
Vertical tilt range	+/-60°	Text display	supplied
Audio support	no	Vandalism resistant	yes
		Scope of delivery:	
		Parts supplied	manual, bag of screws


Product recommendations



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218

