



## ICB-68M3611M5A

Article number: 220592

1/2,5" Network Camera 3840x2160, Day&Night, DOL-WDR 3,6-11 mm, Infrared, IP67

1/2.5" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
4K UHD Resolution 3840x2160, @25/30fps	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 3,6-11mm	Slot for Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE IEEE 802.3af
VCA video analysis, ONVIF event mapping	Integrated connection box with sabotage contact and circuit board
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

## Specifications

Camera:		Features:	
Camera type	Bullet	Menu languages	English, German, French, Korean
Sensor size	1/2.5"	Privacy zones masking	Areas-ON/OFF switchable
Resolution standard	4K Ultra HD	Remote configuration	web browser
Imager	CMOS, Sony STARVIS, Sensor IMX274	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
System	True Day&Night	User interface	Type A (orange / grey)
Sensitivity	0,2 Lux, at F1.5, 40IRE	Mirror function	mirror, flip
Low speed shutter	yes, 1x-10x	Digital Noise Reduction (DNR)	yes
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Network:	
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Interfaces / Inputs / Outputs:	
Flickerless function	yes	Video outputs	no
Backlight compensation	BLC, HLC	External connections	micro SD card slot, Connection board (LSA, RJ45, audio, I / O alarm & Sabotage contacts)
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	Ethernet interface	10Base-T, 100Base-TX
IR cut filter	switchable	Alarm inputs	1
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	Alarm outputs	1
Signal-to-noise ratio	50dB	Serial interfaces	Ethernet
Video:		General:	
Resolution	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Series	eneo Candid Small, eneo LN-Series
Resolution max.	3840x2160	Dimensions (HxWxD)	130,5x82,1x265,1mm
Image display	VerticalView 90°/270°, 4:3, 16:9	Illumination	infrared, 4x High Power LEDs 850nm
Stream types	Multi Streaming	Illumination range	approx. 40m
Image transmission rate max.	30 fps	Colour (housing)	Pantone Cool Gray 1C
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Housing	outdoor
Lens:		Housing material	aluminium
Lens type	Varifocal (motorized)	Weight	1.25kg
Zoom factor	3x	Integrated wall mount	yes
Focal length	3,6 - 11 mm	Power consumption	9,2W
Digital zoom	yes	Blower	yes
MOD (Minimum object distance)	0,5 m	Mounting	wall mount, ceiling mount
Iris control	DC	ONVIF	ONVIF Profile S, ONVIF Profile T
Vertical angle of view	46 - 21 °	Power over Ethernet	IEEE 802.3af
Horizontal angle of view	84 - 40 °	Window heater	no
Features:		Protection rating	IP67
Multicast compliant	yes	SDK	upon request
Motion detector	yes	Hidden cable management	yes
Analysis functions	motion detection, Field detection, Defog, Line detection	Sunshield	yes
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out	Supply voltage	PoE
Audio	2 Way Audio	Temperature range (operation)	-50°C ~ +50°C
Audio support	yes	Text display	supplied
Password protection	yes	Vandalism resistant	no
e-PTZ support	yes	Scope of delivery:	
Internal storage	microSDHC card, microSDXC card	Parts supplied	manual, bag of screws

## Related Products



PM-42A|SKU: 202641

## More product information

Integrated connection box with sabotage alarm contact, Simple wiring, the integrated connection board offers the possibility of network cabling via LSA connection bar or RJ45 socket. Terminal block for connection of alarm contacts and audio.


## Product recommendations



IAD-55G1004MUA|SKU: 216469



IAD-55G1008MUA|SKU: 216472



eneo Site Manager|SKU: 218218

