



VM-FHD12M

Article number: 227599

12" (30cm) LCD Monitor FHD, 1920x1080, LED HDMI, VGA, Composite

Professional 12" (30 cm) LCD monitor	Perfect presentation through digital 3D filtering and noise reduction
Industrial design built to run 24x7x365 continuously	Different video inputs HDMI, VGA, Composite
Maximum resolution 1920x1080 pixels	HD analog multi signal input (TVI, AHD, CVI)
LED Back Light	Supply voltage: 12VDC
Fast response time 5ms	Metal cabinet including stand


Specifications

Display:	
Resolution	1920x1080 (16:9)
Synchronization	internal
Aspect ratio	16:9
Resolution pixels	1920x1080
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	250 cd/m ²
Backlighting	LED
Viewing angle vertical	170 °
Viewing angle horizontal	170 °
Screen size	12,5
Screen Size (cm)	27,65 cm
Pixel format	0,144mm x 0,144mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, 2x HDMI, composite (CVBS), HD-TVI, AHD, CVI
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3,5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	315x326x43mm
Total height with stand	335mm
Mount	VESA standard 75x75mm
Housing material	metal
Housing color	black
Weight	2.3kg
Loudspeaker	2
Power consumption	10W
Supply voltage	12VDC
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, power cord, PSU 100-240VAC, IR remote controller, VGA cable, feet

Related Products



VMC-LCD/WCMB-1 | SKU: 90394



VM-LCDWB2 | SKU: 224229



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

