

# VM-HD19MR

SKU: 229200



19" (48cm) LCD, Professional Monitor, 1280x1024, Protection Glass, Rack Mount, 12V, HDMI

## Main Features

Professional 19" (48 cm) LCD monitor

Built to run 24x7x365 continuously (Industrial Level)

Including protection glass, Anti-Glare-Display 3H

Extended temperature range -30°C ~+85°C

Maximum resolution 1280x1024 pixels

LED Back Light

Fast response time 5ms

Different video inputs HDMI, VGA, BNC (CVBS)

Audio In- and Output

Built-in speakers

Supply voltage: 12VDC

Including 19" mounting frame

## Specifications

Display:	
Aspect ratio	5:4
Resolution Pixels	1280x1024
Contrast ratio typical	1000:1
Reponse time typical	5 ms
Brightness typical	350 cd/m <sup>2</sup>
Backlighting	LED
Viewing angle vertical	178°
Viewing angle horizontal	178°
Screen size (inch)	19"
Screen size (cm)	48 cm

# VM-HD19MR

## Continuation of the specifications

Pixel format	0,294mm x 0,294mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Functions:	
Comb filter	3D Motion Adaptive De-interlace
Menu languages	English
Interfaces / Inputs/ Outputs:	
Video inputs (type)	VGA,HDMI,composite (CVBS)
Video outputs	Composite (CVBS)
Audio inputs	1, 1x 3.5mm jack
Audio output	1x 3,5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	355x482x48mm
Weight	3kg
Mount	VESA standard 100x100mm,VESA standard 75x75mm
Housing material	metal
Housing color	black
Loudspeaker	2
Power consumption	20W
Supply voltage	12VDC
Operating temperature	-30°C ~ +85°C,@ Humidity 10%-90% (non-condensing)
Parts supplied:	
Parts supplied	manual,feet,power cord,PSU 100~240VAC,IR remote controller,HDMI cable

