

# AW1502 Lamp Standard Pole

## Technical Specification

### AW1502

Model No.	Height in metres	Shaft Ø D	Base Ø D2	Payload equip capacity	Recom max equip windload m <sup>2</sup>	Base height C	Door aperture Size L x W	Base plate size H	Holding down bolt centres I	Holding down bolt size	Weight Kgs
AW1502/3	3	139	219	75	0.75m <sup>2</sup>	1100	362x126	405 <sup>2</sup>	350 <sup>2</sup>	M16x200	85
AW1502/4	4	139	219	75	0.75m <sup>2</sup>	1100	362x126	405 <sup>2</sup>	350 <sup>2</sup>	M16x200	123
AW1502/5	5	168	273	75	0.75m <sup>2</sup>	1500	462x126	510 <sup>2</sup>	450 <sup>2</sup>	M20x300	219
AW1502/5LD	5	139	219	50	0.50m <sup>2</sup>	1500	362x126	405 <sup>2</sup>	350 <sup>2</sup>	M16x200	143
AW1502/6	6	168	273	75	0.75m <sup>2</sup>	1500	462x126	510 <sup>2</sup>	450 <sup>2</sup>	M20x300	242
AW1502/6LD	6	139	219	25	0.25m <sup>2</sup>	1500	362x126	405 <sup>2</sup>	350 <sup>2</sup>	M16x200	167
AW1502/7	7	168	273	50	0.50m <sup>2</sup>	1500	462x126	510 <sup>2</sup>	450 <sup>2</sup>	M20x300	269
AW1502/7LD	7	139	219	25	0.25m <sup>2</sup>	1500	362x126	510 <sup>2</sup>	450 <sup>2</sup>	M20x 300	185
AW1502/8	8	168	273	50	0.50m <sup>2</sup>	1500	462x126	510 <sup>2</sup>	450 <sup>2</sup>	M20x300	296
AW1502/8HD	8	219	323	50	0.50m <sup>2</sup>	1900	425x177	630 <sup>2</sup>	550 <sup>2</sup>	M24x400	348
AW1502/9	9	219	323	50	0.50m <sup>2</sup>	1900	425x177	630 <sup>2</sup>	550 <sup>2</sup>	M24x400	419
AW1502/10	10	219	323	50	0.50m <sup>2</sup>	1900	425x177	630 <sup>2</sup>	550 <sup>2</sup>	M24x400	454
AW1502/10HD	10	273	355	75	0.75m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x 600	616
AW1502/11	11	273	355	75	0.75m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x600	661
AW1502/12	12	273	355	75	0.75m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x600	706
AW1502/13	13	273	355	60	0.60m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x600	751
AW1502/14	14	273	355	60	0.60m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x600	796
AW1502/15	15	273	355	50	0.50m <sup>2</sup>	1900	425x177	800 <sup>2</sup>	700 <sup>2</sup>	M27x600	841

### Options

PT No.

Decorative Banding	/B
Screw in Swanneck Adaptor	/SN
Double Door	/DD
Enlarged door aperture	/ENAP
Washer Bottle Conduit	/W
Access Cover plate and Cable restraining bar	/AC
High Security lock	/HS
Altron Lock in lieu of standard lock	/AL

Example Part No.  
**AW1502/15/SN/HS/AL**

All camera mounting plates are DIA 127 with 8 No Ø 8.5 equi-spaced on 101.6 PCD.  
Ø 40 thro' column spacer

For **accessories** refer to page 43

**BASE SIZES ON PAGE 64**

### AW1502

